

STRAUSBERG

INSTRUMENT APPROACH PROCEDURE

RNP RWY 05

TABULAR DESCRIPTION

Approach Segment	Recommended Path Terminator	Way-point Identifier	Coordinates	Fly Over	(True Track°) Mag Track°	Distance (NM)	Turn Direction	Altitude (ft) / Flight Level	Speed Limit (kt IAS)	Vertical Path Angle (°) / TCH (ft)	NAV Specification	Remarks
Initial APCH from RENKI	IF	RENKI	N 52 54 53.43 E 013 57 42.04	N	-	-	-	A4000+	-	-	RNP APCH	-
	TF	AY121	N 52 43 49.56 E 013 53 09.63	N	(T194.0) 191	11.4	-	A3000+	-	-	RNP APCH	-
	TF	AY632	N 52 40 50.21 E 013 51 56.44	N	(T193.9) 191	3.1	-	A3000-	-	-	RNP APCH	-
	TF	AY120	N 52 37 50.64 E 013 50 43.34	N	(T193.9) 191	3.1	-	@ A2000	-	-	RNP APCH	-
	TF	AY110	N 52 33 13.12 E 013 41 57.20	N	(T229.2) 226	7.1	-	@ A2000	-	-	RNP APCH	-
	TF	AY100	N 52 30 12.06 E 013 46 14.65	N	(T139.0) 136	4.0	-	A2000-A1500+	-	-	RNP APCH	-
APCH	TF	MERWU	N 52 32 29.45 E 013 50 34.38	N	(T049.0) 046	3.5	-	A2000-A1500+	-	-	RNP APCH	-
	TF	RW05	N 52 34 35.21 E 013 54 32.80	Y	(T049.1) 046	3.2	-	-	-	-3.5/50	RNP APCH	-
Missed APCH	CF	AY130	N 52 36 58.59 E 013 59 05.38	N	(T049.1) 046	-	-	-	-	-	RNP APCH	-
	TF	AY132	N 52 39 58.14 E 013 58 52.01	N	(T357.4) 354	3.0	-	A2000-	-	-	RNP APCH	-
	TF	RENKI	N 52 54 53.43 E 013 57 42.04	N	(T357.3) 354	15.0	-	@ A4000	-	-	RNP APCH	-

RNAV HOLDING IDENTIFICATION								
Recommended Path Terminator	Holding Fix	Coordinates	Inbound (True Track°) Mag Track°	Max Speed (kt IAS)	Altitude (ft) / Flight Level	Time (MIN) / Distance outbound	Turn Direction	Remarks
HM	RENKI	N 52 54 53.43 E 013 57 42.04	(T166.8) 164	230-	A4000+	1	L	-