

STRAUSBERG

INSTRUMENT APPROACH PROCEDURE

RNP RWY 23

TABULAR DESCRIPTION

| Approach Segment        | Recommended Path Terminator | Way-point Identifier | Coordinates                  | Fly Over | (True Track°) / Mag Track° | Distance (NM) | Turn Direction | Altitude (ft) / Flight Level | Speed Limit (kt IAS) | Vertical Path Angle (°) / TCH (ft) | NAV Specification | Remarks |
|-------------------------|-----------------------------|----------------------|------------------------------|----------|----------------------------|---------------|----------------|------------------------------|----------------------|------------------------------------|-------------------|---------|
| Initial APCH from RENKI | IF                          | RENKI                | N 52 54 53.43 E 013 57 42.04 | N        | -                          | -             | -              | A4000+                       | -                    | -                                  | RNP APCH          | -       |
|                         | TF                          | AY231                | N 52 45 31.54 E 014 06 42.61 | N        | (T149.7) 147               | 10.9          | -              | A3000+                       | -                    | -                                  | RNP APCH          | -       |
|                         | TF                          | AY420                | N 52 42 13.77 E 014 05 51.44 | N        | (T188.9) 186               | 3.3           | -              | @A2000                       | -                    | -                                  | RNP APCH          | -       |
|                         | TF                          | AY400                | N 52 40 15.39 E 014 05 20.88 | N        | (T188.9) 186               | 2.0           | -              | @A2000                       | -                    | -                                  | RNP APCH          | -       |
| APCH                    | TF                          | OCHUS                | N 52 37 58.54 E 014 00 59.61 | N        | (T229.3) 226               | 3.5           | -              | A2000+                       | -                    | -                                  | RNP APCH          | -       |
|                         | TF                          | RW23                 | N 52 35 00.61 E 013 55 21.02 | Y        | (T229.3) 226               | 4.5           | -              | -                            | -                    | -3.5/50                            | RNP APCH          | -       |
| Missed APCH             | CF                          | AY411                | N 52 31 42.38 E 013 49 05.32 | N        | (T229.2) 226               | -             | -              | -                            | -                    | -                                  | RNP APCH          | -       |
|                         | TF                          | AY631                | N 52 34 26.34 E 013 44 15.81 | N        | (T312.9) 310               | 4.0           | -              | -                            | -                    | -                                  | RNP APCH          | -       |
|                         | TF                          | AY120                | N 52 37 50.64 E 013 50 43.34 | N        | (T049.1) 046               | 5.2           | -              | A2000-                       | -                    | -                                  | RNP APCH          | -       |
|                         | TF                          | AY632                | N 52 40 50.21 E 013 51 56.44 | N        | (T013.9) 011               | 3.1           | -              | A3000-                       | -                    | -                                  | RNP APCH          | -       |
|                         | TF                          | RENKI                | N 52 54 53.43 E 013 57 42.04 | N        | (T013.9) 011               | 14.5          | -              | @A4000                       | -                    | -                                  | RNP APCH          | -       |

| RNAV HOLDING IDENTIFICATION |             |                              |                                    |                    |                              |                                |                |         |
|-----------------------------|-------------|------------------------------|------------------------------------|--------------------|------------------------------|--------------------------------|----------------|---------|
| Recommended Path Terminator | Holding Fix | Coordinates                  | Inbound (True Track°) / Mag Track° | Max Speed (kt IAS) | Altitude (ft) / Flight Level | Time (MIN) / Distance outbound | Turn Direction | Remarks |
| HM                          | RENKI       | N 52 54 53.43 E 013 57 42.04 | (T166.8) 164                       | 230-               | A4000+                       | 1                              | L              | -       |