

VATSIM Germany

Standard Instrument Departure Chart

Hamburg
EDDH
SID
RWY 15

Designator	Route	After Take-Off		Remarks
		Climb to	Contact	
EKERN 9D	EKERN NINE DELTA On track 151° GT to 2.5 DME ALF or 1500 ft, whichever is later; LT, on R208 HAM to HAM (Δ); LT, on R344 HAM to EKERN (Δ). GPS/FMS RNAV: [A500+] - DH200[L] - [A1500+; L] - DH201- HAM[L] - EKERN.	5000 ft	Bremen Radar 127.670	
LUB 9D	LÜBECK NINE DELTA On track 151° GT to 2.5 DME ALF or 1500 ft, whichever is later; LT, on R208 HAM to HAM (Δ); RT, on R045 HAM to LUB (Δ). GPS/FMS RNAV: [A500+] - <u>DH200</u> [L] - [A1500+; L] - DH201 - HAM[R] - LUB.			
AMLUH 8D	AMLUH EIGHT DELTA On track 151° GT to 8.2 DME ALF; LT, on R114 LBV to AMLUH (Δ). Cross 8.2 DME ALF at 2800 or above. GPS/FMS RNAV: [A500+] - DH222[A2800+, L] - AMLUH.			Climb with 6.0% / 365 ft per NM or more until passing 2800. PDG due to High Intensity Radio Transmission Area (HIRTA). If unable to comply advise ATC prior to start-up.
RAMAR 3D	RAMAR THREE DELTA On track 151° GT to 7.1 DME ALF; LT, on R212 LUB until crossing R093 HAM; RT, on track 058° LYE to LYE (Δ); RT, on track 120° LYE to RAMAR (Δ). Cross 7.1 DME ALF at 2300 or above. GPS/FMS RNAV: [A500+] - <u>DH208</u> [A2300+; L] - DH209 - DH212[R] - LYE[R] - RAMAR.			
IDEKO 6D	IDEKO SIX DELTA On track 151° GT to 5.0 DME ALF; RT, on bearing 255° WSN inbound WSN until crossing R175 LBV / 25.9 DME HAM; LT, on R185 LBV to IDEKO (Δ). Cross 5.0 DME ALF at 2000 or above. GPS/FMS RNAV: [A500+] - <u>DH202</u> [A2000+; R] - DH216 - DH220[L] - IDEKO.	Bremen Radar 134.250		Climb with 7.0% / 430 ft per NM or more until passing 2000. PDG due to airspace structure. If unable to comply advise ATC prior to start-up.
BASUM 4D	BASUM FOUR DELTA On track 151° GT to 5.0 DME ALF; RT, on bearing 255° WSN inbound WSN until crossing R202 LBV / 32.7 DME HAM; LT, on R206 LBV to BASUM (Δ). Cross 5.0 DME ALF at 2000 or above. GPS/FMS RNAV: [A500+] - <u>DH202</u> [A2000+; R] - DH216 - DH221[L] - BASUM.			
WSN 1D	WESER ONE DELTA On track 151° GT to 5.0 DME ALF; RT, on bearing 255° WSN inbound WSN (Δ). Cross 5.0 DME ALF at 2000 or above. GPS/FMS RNAV: [A500+] - <u>DH202</u> [A2000+; R] - DH216 - WSN.			
LBV 1D	ELBE ONE DELTA On track 151° GT to 5.0 DME ALF; RT, on bearing 255° WSN inbound WSN until crossing R132 LBV / 17.0 DME HAM; RT, on R138 LBV to LBV (Δ). Cross 5.0 DME ALF at 2000 or above. GPS/FMS RNAV: [A500+] - <u>DH202</u> [A2000+; R] - DH216 - DH217[R] - LBV.			

(Sample: DH200 fly-over way point)

Remain on TWR frequency until passing 2000ft, then contact Bremen Radar.

