

PANS-OPS INSTRUMENT APPROACH CHART

AD ELEV 73


ILS or LOC RWY 26
NORDHOLZ (ETMN)

BREMEN RADAR 371.750 124.075		NORDHOLZ RADAR 278.350 129.850		NORDHOLZ TOWER 315.700 131.250			
TACAN / LOCALIZER CH 118X / INOW 111.750	APP COURSE 256°	GS INTCP ALT 1600	GS 3.0° (5.2%)	DA See CAT	TDZE 64	ALS-LENGTH 900 M	LDA 8004

NOTE:

- a) PROCEDURE LIMITED TO 230 KIAS.
- b) CIRCLING NOT AUTHORIZED NORTH OF RWY.
- c) RACETRACK PROCEDURE TURN 1 MIN.

IAF
53°47.11'N
008°48.37'E




EMERG SAFE ALT 100 NM 2700

MISSED APPROACH

Climb straight ahead to 2000 ft. When passing 1000 ft turn left and rehome NDB.

TA 5000



CATEGORY	A	B	C	D
S-ILS 26	264 - 0.8/550 200 (200-0.8/1.2)			
S-LOC 26	480 - 0.8 416 (500-0.8/1.6)		480 - 1.2 416 (500-1.2/2.0)	
b CIRCLING	560 - 1.6 487 (500-1.6)	570 - 1.6 497 (500-1.6)	780 - 3.6 707 (800-3.6)	930 - 4.8 857 (900-4.8)

ILS or LOC RWY 26

53°46.06'N
008°39.51'E

NORDHOLZ (ETMN)